

## Keramikbrennöfen STUDIO + PROFITHERM

02.11.2013

Art-Nr	Modell	Nutzinhalt Liter	Innenmaße			Außenmaße			Tmax °C	Gewicht kg	Leistung kW	Spannung V	Sicherung A	Netzstecker
			Durchmesser mm	Höhe		B	mm T	H						
<b>STUDIO:</b>														
10305200	ST 52 H	52	430	340		570	730	750	1200	45	3,60	230	16	Schuko
10305204	ST 52 HD	52	430	340		570	730	750	1260	45	4,50	400 2N	2 x 16	CEE 16
10306800	ST 68 H	70	430	460		570	730	870	1100	55	3,60	230	16	Schuko
10306804	ST 68 HD	70	430	460		570	730	870	1260	55	5,70	400 3N	3 x 16	CEE 16
10308504	ST 85 HD	85	480	460		630	780	840	1260	65	5,70	400 3N	3 x 16	CEE 16
10310304	ST 103 HD	105	480	570		630	780	950	1260	75	7,20	400 3N	3 x 16	CEE 16
10312004	ST 120 HD	122	520	570		670	820	950	1260	85	7,20	400 3N	3 x 16	CEE 16
10314504	ST 145 HD	145	570	570		720	870	950	1260	95	9,60	400 3N	3 x 20	CEE 32
10317304	ST 173 HD	177	570	690		720	870	1040	1260	100	10,50	400 3N	3 x 20	CEE 32
10320804	ST 208 HD	209	620	690		770	900	1040	1260	115	13,30	400 3N	3 x 25	CEE 32
10325004	ST 250 HD	253	680	690		840	960	1040	1260	130	13,30	400 3N	3 x 25	CEE 32
10318804	ST 188 HS	188	750	520	570	980	800	980	1260	110	11,00	400 3N	3 x 20	CEE 32
<b>PROFITHERM:</b>														
10001200	PY 12	12	230	230	230	380	470	580	1300	25	2,40	230	16	Schuko
10003000	PY 30 H	30	400		230	570	730	640	1320	35	3,60	230	16	Schuko
10004500	PY 45 H	45	400		340	570	730	750	1300	45	3,60	230	16	Schuko
10005600	PY 56 H	57	460		340	630	780	920	1200	55	3,60	230	16	Schuko
10005604	PY 56 HD	57	460		340	630	780	920	1320	55	4,50	400 2N	2 x 16	CEE 16
10007500	PY 75 H	77	460		460	630	780	840	1200	65	3,60	230	16	Schuko
10007504	PY 75 HD	77	460		460	630	780	840	1320	65	5,70	400 3N	3 x 16	CEE 16
10009504	PY 95 HD	96	460		570	630	780	950	1320	75	7,20	400 3N	3 x 16	CEE 16
10011004	PY 110 HD	112	500		570	670	820	950	1320	85	7,20	400 3N	3 x 16	CEE 16
10013504	PY 135 HD	137	550		570	720	870	950	1320	95	9,60	400 3N	3 x 20	CEE 32
10016304	PY 163 HD	166	550		690	720	870	1040	1320	100	10,50	400 3N	3 x 20	CEE 32
10019504	PY 195 HD	195	600		690	770	900	1040	1320	115	13,30	400 3N	3 x 25	CEE 32
10023604	PY 236 HD	238	660		690	840	960	1040	1320	130	13,30	400 3N	3 x 25	CEE 32
<b>PROFITHERM mit Schwingdeckel und solider Reling:</b>														
10108004	PY 80 HS	80	470		460	630	780	840	1320	70	5,70	400 3N	3 x 16	CEE 16
10110004	PY 100 HS	99	470		570	630	780	950	1320	80	7,20	400 3N	3 x 16	CEE 16
10111504	PY 115 HS	114	510		570	670	820	950	1320	90	7,20	400 3N	3 x 16	CEE 16
10113804	PY 138 HS	142	740	510	460	0	670		1320	97	9,60	400 3N	3 x 20	CEE 32
10114004	PY 140 HS	139	560		570	720	870	950	1320	100	9,60	400 3N	3 x 20	CEE 32
10117004	PY 170 HS	174	665		500	920	1030	870	1320	100	9,60	400 3N	3 x 20	CEE 32
10117204	PY 172 HS	172	730	500	570	100	800	960	1320	100	9,60	400 3N	3 x 20	CEE 32
10121004	PY 210 HS	217	665		625	920	1030	990	1320	120	11,00	400 3N	3 x 20	CEE 32
10125504	PY 255 HS	260	665		750	920	1030	1120	1320	135	13,30	400 3N	3 x 25	CEE 32
10129004	PY 290 HS	290	730		690	1000	1100	1130	1320	160	15,60	400 3N	3 x 25	CEE 32
10145004	PY 450 HS	450	665	1040	750	1350	1050	1120	1320	200	22,00	400 3N	3 x 32	CEE 32